

Cat® Lift Trucks.

Your partner in materials handling.

	DP100N / DP120N					DP100N	DP120N
Mast Type	h3	h1	h4	h2	Tilt angle (fwd./back)	Q @ c = 600mm kg	Q @ c = 600mm kg
Simplex	3072	3087	4486	72	15°/12°	10000	12000
	3572	3337	4986	72	15°/12°	10000	12000
	3772	3437	5186	72	15°/12°	10000	12000
	4072	3587	5486	72	15°/12°	10000	12000
	4572	3837	5986	72	15°/12°	10000	12000
	5072	4087	6486	72	15°/12°	10000	12000
	5572	4337	6986	72	15°/12°	10000	12000
	6072	4637	7486	72	6°/6°	9800	11800


	DP135N / DP150N					DP135N	DP150N
Mast Type	h3	h1	h4	h2	Tilt angle (fwd./back)	Q @ c = 600mm kg	Q @ c = 600mm kg
Simplex	3088	3332	4927	88	15°/12°	13500	15000
	3588	3632	5427	88	15°/12°	13500	15000
	3788	3732	5627	88	15°/12°	13500	15000
	4088	3882	5927	88	15°/12°	13500	15000
	4588	4132	6427	88	15°/12°	13500	15000
	5088	4382	6927	88	15°/12°	13500	15000
	5588	4682	7427	88	15°/12°	13500	15000
	6088	4932	7927	88	6°/6°	13300	14600

	DP160N					
Mast Type	h3	h1	h4	h2	Tilt angle (fwd./back)	Q @ c = 600mm kg
Simplex	3092	3530	4927	92	15°/12°	16000
	3592	3780	5427	92	15°/12°	16000
	3792	3880	5627	92	15°/12°	16000
	4092	4030	5927	92	15°/12°	16000
	4592	4280	6427	92	15°/12°	16000
	5092	4530	6927	92	15°/12°	16000
	5592	4830	7427	92	15°/12°	16000
	6082	5080	7927	92	6°/6°	15800



Mast Performance and Capacity

- h1 Height with mast lowered
- h2 Standard free lift
- h3 Lift height
- h4 Height with mast raised
- h5 Full free lift
- Q Lifting capacity, rated load
- c Load centre (distance)



DP100N - DP120N - DP135N - DP150N DP160N

Preliminary specifications

Engine powered lift trucks
10.0 - 16.0 tonnes

info@catlifttruck.com
www.catlifttruck.com

CESC1682-H(01/15)p
©2015, MCFE. All Rights Reserved. CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

Printed in The Netherlands

NOTE: Performance specifications may vary depending on standard manufacturing tolerances, vehicle condition, types of tyres, floor or surface conditions, applications, or operating environment. Trucks may be shown with non-standard options. Specific performance requirements and locally available configurations should be discussed with your Cat lift trucks Dealer. Cat Lift Trucks follows a policy of continual product improvement. For this reason, some materials, options and specifications could change without notice.



